


Brisa™ Linear Bow Surface Mount **FB9314LEC**

Page 1 of 1

Wall Mounted T5 Fluorescent ADA Compliant



Fixture Ordering Information

Catalog No.	Description	Finish	Wattage	Volts	Lamp
FB9314LEC1	Linear Bow Surface Mount Dimming	Satin aluminum	14W	120V	(3) T5
FB9314LEC2	Linear Bow Surface Mount Dimming	Satin aluminum	14W	277V	(3) T5

Diffuser Ordering Information

Catalog No.	Description	Finish	Dimensions (Nominal)
FBA9	Acrylic Bow Diffuser	Opal	9" X 24"
FBG9	Glass Bow Diffuser	Opal	9" X 24"

Features

- Housing Sides and ends:** Die-cast aluminum.
- Back Pan:** Stamped 18ga. (0.048") sheet metal.
- Diffuser:** Bowed opal glass or opal acrylic
- Optics:** Internal white acrylic diffuser covers slots on housing sides and ends.

Mounting

Fixture Mounts directly to 4" octagonal junction box.

Electrical

- Ballast-Fixture:** Has (1) 1-lamp ballast and (1) 2-lamp ballast, allowing for separate switching.

A. Lutron Dimming 120V & 277V	1 Lamp		2 Lamp	
Voltage	120V	277V	120V	277V
Total Input Watts	20W	10W	38W	17W
Max. Line Current (Amps)	0.17A	0.08A	0.32A	0.14A
Power Factor	>0.95	>0.95	>0.95	>0.95
THD	<20%	<20%	<20%	<20%
Min. Starting Temp	50°F, -10°C		50°F, -10°C	
Dimming Range	100%-10%		100%-10%	

- Luminaire-Ballast Disconnect:** Meets NEC 410.130(G) and CEC Disconnect Requirements.

Lampholders

Fluorescent: Mini Bi-Pin, G5 Base

Lamping (by others)

General Electric	Osram/Sylvania	Philips
(1) 14W T5 Linear Fluorescent		
F14W/T5/*/ECO	FP14/*	F14T5/*/ALTO
*Manufactures Color Temperaturæ Designation		

Finish

Satin Aluminum

Labels

cULus Listed. Suitable for Damp Locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2007 Genlyte Group LLC • 0907

LIGHTOLIER